



Blisbond Pro3 4K Portable Dual-Screen Action Camera

Sale Price: 14000.0

PRODUCT ID: 0008362

Key Features

Image	4K 60/30, 1080P 60/30 Photo Resolution:20M/16M/14M/12M @ JPEG
Video	4K 60/30, 2.7K 30, 1080P 60, 1080P 30, 720P120@ MOV, H.264
Display	Front Color Screen: Front Color Screen, 1.5-inch IPS high-definition screen Rear Main Screen: Rear Main Screen, 2.0-inch IPS touch screen
USB Port	Type-C 5pin + TF card slot
Memory	Micro SD card with a speed of C10 / U1 or above, maximum capacity of 64G

Battery Information

Removable	Yes
type	lithium battery
Capacity	1800mAh / 6.66Wh rechargeable
Charging Time	Battery Life: Approximately 180 minutes @ 4K30 (measured with the screen saver on and WIFI off)

Special Features

Wi-Fi	iSmart DV2 supports Android and iOS systems 2.4G-2.48G, 802.11a/b/g/n/ac
Water Resistant	IP68, 30-meter waterproof (A dedicated waterproof case is required)

Key Features

Others

Handheld Design: Shoot Anytime and Anywhere
Vertical Shooting: Facilitate Uploading and Sharing on More Platforms
More Intuitive Composition for Direct Shooting
Six-axis Image Stabilization: Stay Steady Even When You're Excited
Main Control Scheme:i-Catch V35AX
Lens Module:Sony IMX386, 12 million pixels, 150° wide-angle lens
Regular recording, vertical shooting, pre-recording, loop recording, time-lapse recording, slow motion
Single shot capture, timed shooting, high-speed continuous shooting, time-lapse shooting, long exposure
Low light mode, driving mode, snowy mode, snorkeling mode, etc. are available
Horizontal correction is supported
Supports three angle adjustments: wide/medium/narrow
Wind Noise Reduction
Wireless Remote Control
Built-In: Built-in, Built-in waterproof microphone
External: External, Compatible with a dedicated TYPE-C external MIC (Optional)
Compatible with a dedicated wireless MIC (Optional)
8 ohms, 0.5-watt speaker
Audio:ACC / Stereo
Manual setting is supported
LED charging/working indicator light
Supports automatic screen-off after 1 minute/3 minutes/5 minutes of inactivity
Supports automatic shutdown after 1 minute/3 minutes/5 minutes of inactivity
Multi-language system operation is supported
Power Input:5V 1~2A
Storage Temperature:-20°C~60°C
Operating Temperature:-10°C~40°C

Warranty Information

Manufacturing Warranty

1-Year Brand Warranty