

Dahua 2MP Smart Dual Light HDCVI Bullet 30 MTR IR Distance, Lens 3.6mm (Plastic)#DH-HAC-B1A21P-U-IL

Sale Price: 1700.0



PRODUCT ID: 01839

— General

Casing	Metal front cover + plastic rear barrel + metal bracket
Dimensions	146.1 mm × 70.0 mm × 69.8 mm (5.75" × 2.76" × 2.75")
Weight	0.23 kg (0.51 lb)
Pan/Tilt/Rotation	Pan: 0°–360° Tilt: 0°–90° Rotation: 0°–360°
Operating Conditions	–40 °C to +60 °C (–40 °F to +140 °F)
Storage Conditions	–40 °C to +60 °C (–40 °F to +140 °F)
Power Supply	12 VDC ± 30%
Power Consumption	Max 3.3 W (12 VDC, WLED on)

Camera

Image Sensor	2 MP CMOS
Effective Pixels	1920 (H) × 1080 (V)
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/25 s–1/100000 s NTSC: 1/30 s–1/100000 s
Minimum Illumination	0.02 lux@F2.0 (Color, 30 IRE); 0.002 lux@F2.0 (B/W, 30 IRE); 0 lux (Illuminator on)
S/N Ratio	>65 dB
IR Distance	IR: 30 m (98.43 ft); Warm light: 20 m (65.62 ft)
IR On/Off Control	Auto / Manual

General

IR LEDs	2 (Warm light);2 (IR light)
---------	-----------------------------

Lens

Lens Type	Fixed-focal
Mount Type	M12
Focal Length	2.8 mm; 3.6 mm; 6 mm
Max Aperture	F2.0
Angle of View	2.8 mm: H: 100°; V: 54°; D: 117° 3.6 mm: H: 80°; V: 43°; D: 94° 6 mm: H: 43°; V: 24°; D: 50°
Close Focus Distance	2.8 mm: 0.5 m (1.64 ft) 3.6 mm: 0.8 m (2.62 ft) 6 mm: 2.4 m (7.87 ft)

Video

Resolution	1080p (1920 × 1080); 960H (960 × 576/960 × 480)
Frame Rate	CVI: PAL: 1080p@25 fps NTSC: 1080p@30 fps AHD: PAL: 1080p@25 fps NTSC: 1080p@30 fps TVI: PAL: 1080p@25 fps NTSC: 1080p@30 fps CVBS: PAL: 960H NTSC: 960H
Video Output	Video output choices of CVI/TVI/AHD/CVBS by one BNC port
Day/Night	Auto(ICR)/Color/B/W
BLC Mode	BLC; HLC; DWDR
Gain Control	Auto/Manual
Noise Reduction	2D NR

Interface

Audio Interface	Video output choices of CVI/TVI/AHD/CVBS by one BNC port
Video Interface	One channel built-in mic

Special Features

General

Features

Smart Dual Light.
30 m illumination distance.
Super Adapt.
Built-in MIC.
IP67

Warranty

Warranty

1 Year