

Uniview UAC-T122-AF28LM 2MP LightHunter HD IR Fixed Turret Analog Camera

Sale Price: 2200.0



PRODUCT ID: 0008658

Brand	Uniview
Model	UAC-T122-AF28LM
Type	2MP LightHunter HD IR Fixed Turret Analog Camera
Pixel	2MP
Size	1/2.9"
Minimum illumination	0.005 lux (F1.6, AGC ON) 0 lux (IR on)
Lens	2.8mm
Lens mount	M12
Angle of view	H: 101.5° V: 56.9° D: 117.4°
Illuminator	Two IR illuminators
Illumination distance	40m
Lifetime	≥60,000 hours
Resolution	1080P: 1920(H)×1080(V) 720P: 1280(H) ×720(V)
Frame rate	TVI/AHD/CVI: 1080P@25fps (default), 1080P@30fps; 720P@25fps, 720P@30fps CVBS: PAL, NTSC
Shutter Time	PAL: 1/25s-1/50000s NTSC: 1/30s-1/50000s
Exposure Mode	Four modes: Global (default), BLC, HLC, DWDR
Day/Night	Three modes: Auto (default), Day, Night
Digital Noise Reduction	2D/3D
White Balance	Two modes: Auto (default), Manual
WDR	DWDR
Smart IR	Support

Flip	Supports 180° horizontal flip, 180° vertical flip
Defog	Digital Defog
Microphone	Built-in Mic
Camera Audio	TVI: 1080P@25fps, 1080P@30fps CVI: 1080P@25fps, 1080P@30fps
Power	5.5mm power interface
Video Output	BNC, supports TVI/AHD/CVI/CVBS
Power	DC 12V (±25%), with reverse polarity protection, Max 3.2W
Temperature	-30°C to 60°C (-22°F to 140°F)
Humidity	≤95% (RH, non-condensing)
Surge Protection	4kV
Ingress Protection	IP67
Dimensions	Φ111mm*98mm (diameter*height)
Weight	334g (0.74lb)
Body Material	Metal+Plastic
Mount	Surface mount (default), optional backbox, wall mount bracket
Certification	CE, FCC, UL
Warranty Details	1-Year Brand Warranty