



Dahua 2MP Dome HDCVI 25 MTR IR Distance, Lens 3.6 MM (Plastic)#DH-HAC-HDW1200TRQP

Sale Price: 1900.0

PRODUCT ID: 01822

General

Casing	Plastic
Dimensions	Φ97.1 mm × 93.0 mm (Φ3.82" × 3.66")
Weight	0.17 Kg (0.37lb)
Pan/Tilt/Rotation	Pan: 0°-360° Tilt: 0°-78° Rotation: 0°-360°
Operating Conditions	-40°C to +50°C (-40°F to 122°F); <95% (non-condensation)
Storage Conditions	-40°C to +50°C (-40°F to 122°F); <95% (non-condensation)
Power Supply	12V ±30% DC
Power Consumption	Max 2.6 W (12V DC, IR on)

Camera

Image Sensor	1/2.7 inch CMOS
Effective Pixels	2MP
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/25s-1/100000s NTSC: 1/30s-1/100000s
Minimum Illumination	0.02 Lux/F1.9, 30IRE, 0 Lux IR on
S/N Ratio	>65dB
IR Distance	25 m (82.0 ft)
IR On/Off Control	Auto; manual

Lens

Lens Type	Fixed -Focal
Mount Type	M12

General

Focal Length	2.8mm; 3.6mm
Max Aperture	2.8 mm: F1.9 3.6 mm: F2.0
Angle of View	2.8 mm: H: 101°; V: 54°; D: 119° 3.6 mm: H: 84°; V: 45°; D: 100°
Close Focus Distance	2.8 mm: 0.5 m (1.64 ft) 3.6 mm: 0.8 m (2.62 ft)

Video

Resolution	1920(H)×1080(V)
Frame Rate	CVI: 1080P@25/30fps; 720P@25/30fps; 720P@50/60fps; AHD: 1080P@25/30fps; 720P@25/30fps; TVI: 1080P@25/30fps; 720P@25/30fps; 720P@50/60fps; CVBS: 960H
Video Output	Video output choices of CVI/TVI/AHD/CVBS by one BNC port
Day/Night	Auto switch by ICR
BLC Mode	BLC/HLC/DWDR
BLC Mode	BLC/HLC/DWDR
Gain Control	Auto; manual
Noise Reduction	2D NR

Interface

Audio Interface	Built-in mic (-A)
-----------------	-------------------

Warranty

Warranty	1 Year
----------	--------