



Dahua 2MP Full Time Color Bullet HDCVI Camera 40 MTR IR Distance, Lens 3.6 MM With Built In Mic (Metal)#DH-HAC-HFW1239TLMP-A-LED-S2

Sale Price: 3300.0

PRODUCT ID: 01835

General

Casing	Metal front cover + plastic main body + metal bracket
Dimensions	198.4mm×80.2mm×76.2mm (7.81"×3.16"×3.00")
Weight	0.3Kg
Pan/Tilt/Rotation	Pan: 0°-360° Tilt: 0°-180° Rotation: 0°-360°
Operating Conditions	-40°C to +60°C (-40°F to 140°F); < 95% (non-condensation)
Storage Conditions	-40°C to +60°C (-40°F to 140°F); < 95% (non-condensation)
Power Supply	12V ±30% DC
Power Consumption	Max 5W (12V DC, white light on)

Camera

Image Sensor	1/2.8 inch 2.16 Mega Pixels CMOS
Effective Pixels	1920 (H)×1080 (V), 2MP
Electronic Shutter Speed	PAL:1/25s-1/100000s NTSC:1/30s-1/100000s
Minimum Illumination	0.005Lux/F1.6, 30IRE, 0Lux white Light on
IR Distance	Distance up to 40m (131.23ft)
IR On/Off Control	Auto; Manual
IR LEDs	2

Lens

Lens Type	Fixed-focal Fixed iris
Mount Type	M12

General

Focal Length	2.8m/3.6mm
Max Aperture	F1.6
Angle of View	2.8mm: 126.2°×106.0°×56.5° (diagonal×horizontal×vertical) 3.6mm: 103.6°×86.9°×46.3° (diagonal×horizontal×vertical)
Close Focus Distance	2.8mm: 0.6m (1.97ft) 3.6mm: 1.2m (3.94ft)

Video

Resolution	1080P (1920×1080); 720P (1280×720); 960H (704×576/704×480)
Frame Rate	CVI: PAL: 1080@25fps, 720@25fps, 720@50fps; NTSC: 1080@30fps, 720@30fps, 720@60fps AHD: PAL: 1080@25fps,720@25fps; NTSC: 1080@30fps,720@30fps TVI: PAL: 1080@25fps,720@25fps,720@50fps; NTSC: 1080@30fps,720@30fps,720@60fps CVBS: PAL: 960×576H; NTSC: 960×480H
Video Output	Video output choices of CVI/TVI/AHD/CVBS by one BNC port
BLC Mode	BLC/HLC/WDR
Gain Control	Auto; Manual
Noise Reduction	2D NR

Interface

Audio Interface	Built-in mic(-A)
-----------------	------------------

Warranty

Warranty	1 Year
----------	--------