



Dahua 5MP Smart Dual Light HDCVI Bullet 40 MTR IR Distance, Lens 3.6 MM With Built In Mic (Metal+Plastic)#DH-HAC-HFW1500TLMP-IL-A

Sale Price: 3850.0

PRODUCT ID: 01859

General

Casing	Metal front cover + plastic rear barrel + metal bracket
Dimensions	198.4 mm × 80.2 mm × 76.2 mm (7.81" × 3.16" × 3")
Weight	0.3 kg (0.66 lb)
Pan/Tilt/Rotation	Pan: 0°-360° Tilt: 0°-90° Rotation: 0°-360°
Operating Conditions	-40 °C to +60 °C (-40 °F to +140 °F)
Storage Conditions	-40 °C to +60 °C (-40 °F to +140 °F)
Power Supply	12 VDC ± 30%
Power Consumption	Max 4.5 W (12 VDC, WLED on)

Camera

Image Sensor	5 MP CMOS
Effective Pixels	2880 (H) × 1620 (V)
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/25 s-1/100000 s NTSC: 1/30 s-1/100000 s
Minimum Illumination	0.05 lux@F1.6 (Color, 30 IRE) 0.005 lux@F1.6 (B/W, 30 IRE) 0 lux (Illuminator on)
S/N Ratio	More than 65dB
IR Distance	IR: 40 m (131.23 ft) Warm Light: 40 m (131.23 ft)
IR On/Off Control	Auto / Manual
IR LEDs	2 (Warm light);2 (IR light)

Lens

Lens Type	Fixed-focal
-----------	-------------

General

Mount Type	M12
Focal Length	3.6 mm
Max Aperture	F1.6
Angle of View	2.8 mm: H: 106°; V: 56°; D: 125° 3.6 mm: H: 92°; V: 48°; D: 109°
Close Focus Distance	3.6 mm: 1.3 m (4.27 ft)

Video

Resolution	5M (2880 × 1620); 4M (2560 × 1440); 1080p (1920 × 1080); 960H (960 × 576/960 × 480)
Frame Rate	CVI: PAL: 5M@25 fps; 4M@25 fps; 1080p@25 fps; NTSC: 5M@25 fps; 4M@30 fps; 1080p@30 fps AHD: PAL: 4M@25 fps; NTSC: 4M@30 fps TVI: PAL: 4M@25 fps; NTSC: 4M@30 fps CVBS: PAL: 960H; NTSC: 960H
Video Output	Video output choices of CVI/TVI/AHD/CVBS by one BNC port
Day/Night	Auto(ICR)/Color/B/W
BLC Mode	BLC; HLC; DWDR
Gain Control	Auto/Manual
Noise Reduction	2D NR

Interface

Audio Interface	Video output choices of CVI/TVI/AHD/CVBS by one BNC port
Video Interface	One channel built-in mic

Special Features

Features	Smart Dual Light. 40 m illumination distance. Super Adapt. Built-in MIC. IP67
----------	---

Warranty

General

Warranty

1 Year