



## Dahua 5MP Smart Dual Light HDCVI Bullet 20 MTR IR Distance, Lens 3.6 MM With Built In Mic (Plastic)#DAHUA DH-HAC-HFW1500CLP-IL-A

Sale Price: 2600.0

PRODUCT ID: 01858

### General

Casing	Plastic
Dimensions	163.4 mm × 69.7 mm × 70 mm (6.43" × 2.74" × 2.76")
Weight	0.19 kg (0.42 lb)
Pan/Tilt/Rotation	Pan: 0°–360° Tilt: 0°–90° Rotation: 0°–360°
Operating Conditions	–40 °C to +60 °C (–40 °F to +140 °F)
Storage Conditions	–40 °C to +60 °C (–40 °F to +140 °F)
Power Supply	12 VDC ± 30%
Power Consumption	Max 4.5 W (12 VDC, WLED on)

### Camera

Image Sensor	5 MP CMOS
Effective Pixels	2880 (H) × 1620 (V) Max 25 fps@5MP
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/25 s–1/100000 s NTSC: 1/30 s–1/100000 s
Minimum Illumination	0.05 lux@F1.6 (Color, 30 IRE) 0.005 lux@F1.6 (B/W, 30 IRE) 0 lux (Illuminator on)
S/N Ratio	>65 dB
IR Distance	IR: 20 m (65.62 ft) Warm Light: 20 m (65.62 ft)
IR On/Off Control	Auto / Manual
IR LEDs	2 (Warm light);2 (IR light)

### Lens

Lens Type	Fixed-focal
-----------	-------------

## General

Mount Type	M12
Focal Length	2.8 mm;3.6 mm
Max Aperture	F1.6
Close Focus Distance	2.8 mm: 0.8 m (2.62 ft) 3.6 mm: 1.3 m (4.27 ft)

## Video

Resolution	5M (2880 × 1620); 4M (2560 × 1440); 1080p (1920 × 1080); 960H (960 × 576/960 × 480)
Frame Rate	CVI: PAL: 5M@25 fps; 4M@25 fps; 1080p@25 fps NTSC: 5M@25 fps; 4M@30 fps; 1080p@30 fps AHD: PAL: 4M@25 fps; NTSC: 4M@30 fps TVI: PAL: 4M@25 fps; NTSC: 4M@30 fps CVBS: PAL: 960H; NTSC: 960H
Video Output	Video output choices of CVI/TVI/AHD/CVBS by one BNC port
Day/Night	Auto(ICR)/Color/B/W
BLC Mode	BLC; HLC; DWDR
Gain Control	Auto/Manual
Noise Reduction	2D NR

## Interface

Audio Interface	1-channel built-in MIC
Video Interface	Video output choices of CVI/TVI/AHD/CVBS by one BNC port

## Special Features

Features	Smart Dual Light. Super Adapt. Built-in MIC. IP67, 12 VDC.
----------	---

## Warranty

Warranty	1 Year
----------	--------