Dahua 08 Channel Wizsense XVR (1 Sata UP to 6TB) 5MP, 4MP, 1080P H.265 UP To 6 MP Camera IP Supports #DH-XVR1B08H-I

Sale Price: 8500.0

PRODUCT ID: 01801

System

Main Processor	Embedded Processor
Operating System	Embedded LINUX

Audio and Video

IP Camera Input	8+2 each channel up to 12MP
Two-Way Talk	Reuse audio in/out, RCA

Display

Interface	1 HDMI ,1 VGA
Resolution	1920×1080, 1280×1024, 1280×720
Multi-Screen Display	When IP extension mode not enabled: 4CH: 1/4 When IP extension mode enabled: 4CH: 1/4/6
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording

Recording

Compression	H.265+/H.265/H.264+/H.264
Resolution	5M-N, 4M-N, 1080P, 1080N, 720P, 960H, D1, CIF
Record Rate	Main Stream: 4CH: the 1st channel 5M-N(1~10fps) Sub stream: CIF/QCIF (1~15fps)
Bit Rate	32Kbps ~ 6144Kbps Per Channe
Record Mode	Manual, Schedule (General, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop
Record Interval	1 ~ 60 min (default: 60 min), Pre-record: 1 ~ 30 sec, Postrecord: 10 ~ 300 sec

Video Detection And Alarm

System

Trigger Event	Recording, PTZ, Tour, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips
Video Detection	Motion Detection, MD Zones: 396 (22 × 18), Video Loss, Tampering and Diagnosis

Playback And Backup

Sync Playback	4CH: 1/4
Search Mode	Time /Date, Alarm, MD and Exact Search (accurate to second)
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Repeat, Shuffle, Backup Selection, Digital Zoom
Backup Mode	USB Device/Network

Third Party Support

Third Party Support	Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek, and more

Network

Interface	1 RJ-45 Port (100M)
Network Function	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter ,DDNS, FTP, Alarm Server, P2P,IP Search (Supports Dahua IP camera, DVR, NVS, etc.)
Maximum User Access	128 users
Smart Phone	iPhone, iPad, Android
Interoperability	ONVIF 16.12, CGI Conformant

Storage

Internal HDD	1 SATA Port, up to 6TB capacity

Auxiliary Interface

USB	2x USB 2.0

Power

Power Supply	DC12V/1.5A

System

Power Consumption	<10W

Component Environment

Operational Conditions	-10°C ~ +45°C (+14°F ~ +113°F), 10~ 90% RH
Storage Conditions	-20°C ~ +70°C (-4°F ~ +158°F) , 0~ 90% RH

Construction

Dimensions	197mm×192mm×41mm (7.8“×7.6”×1.6“)
Net Weight	0.54kg