

Hikvision DS-2CE16G0T-LPFS (3.6mm) (3MP) 2K Smart Hybrid Light Audio Fixed Mini Bullet CC Camera



Sale Price: 2000.0

PRODUCT ID: **09735**

Camera	
Angle Adjustment	Pan: 0 to 360°, Tilt: 0 to 90°, Rotation: 0 to 360°
Signal System	PAL/NTSC
Max. Resolution	2304 (H) × 1296 (V)
Min. Illumination	0.01 Lux @ (F1.6, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50,000 s; NTSC: 1/30 s to 1/50,000 s
Day & Night	ICR
Lens	
Focal Length & FOV	2.8 mm, horizontal FOV: 105°, vertical FOV: 60°, diagonal FOV: 129° 3.6 mm, horizontal FOV: 89°, vertical FOV: 47°, diagonal FOV: 107°
Lens Mount	M12
Illuminator	
Supplement Light Type	Smart,IR,White Light
Supplement Light Range	IR: Up to 25 m White Light : Up to 20 m
Image	
Image Settings	Brightness, Sharpness, Smart IR
Frame Rate	TVI: 2K @20fps, 1080P @25fps/30fps AHD: 1080P @25fps/30fps CVI: 1080P @25fps/30fps CVBS: PAL/NTSC
Day/Night Mode	Auto/Color
Wide Dynamic Range (WDR)	Digital WDR
Image Enhancement	DWDR/BLC/HLC/Global
White Balance	Auto/Manual
AGC	Yes

Interface Eelectrical	
Video Output	Switchable TVI/AHD/CVI/CVBS
General Information	
Material	Plastic
Dimensions	138.8 mm × 60.9 mm × 57.9 mm (5.47" × 2.4 " × 2.3")
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less (non-condensing)
Communication	HIKVISION-C
Language	English
Power Supply	12 VDC ± 25%, max. 3.9 W,