Dahua 32 Channel Wizsense XVR (2 Sata UP to 16TB) 4K HDMI, H265/H.265+, UP To 5MP Camera Supports #DH-XVR5232AN-I3

Sale Price: 44000.0

PRODUCT ID: 01846

System

Main Processor	Industrial-grade processor
Operating System	Embedded LINUX

Audio and Video

IP Camera Input	Up to 32 channels of IPC access 32 channels (analog channels are converted to IP channels) incoming bandwidth: 128 Mbps, recording bandwidth: 128 Mbps and outgoing bandwidth: 128 Mbps
Two-Way Talk	Yes (share the same audio input with the first channel)

Display

Interface	1 HDMI, 1 VGA, 1 TV
Resolution	VGA: 1920 × 1080, 1280 × 1024, 1280 × 720 HDMI: 3840 × 2160, 1920 × 1080, 1280 × 1024, 1280 × 720
Multi-Screen Display	1/4/8/9/16/25/36
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording

Recording

Compression	Video Compression: AI Coding; Smart H.265+; H.265; Smart H.264+; H.264 Audio Compression: G.711a; G.711u; PCM
Record Rate	Main stream: 5M-N@(1fps–10fps); 4M-N,1080p@(1fps–15fps); 1080N, 720p, 960H, D1,CIF@(1fps–25/30fps) Sub stream: D1, CIF@(1fps–15fps)
Bit Rate	32 kbps–6144 kbps
Record Mode	General, motion detection; intelligent; alarm; POS

Playback And Backup

MUNSHIGANJ IT

Hotline-09614-502244

We Connect Whole Narayanganj...

A Super Store Of Computer & Electronics Accessoriess

Sales-01979490143, Corporate- 01979999722

194, Banghabandhu Road, Shomobay New Market (2nd Floor)

MITCare- 01979490145, Warranty-0197949 0146

Shop No. 117-118,103-104, Chasara, Narayanganj-1400

CCTV-01979490147, Web team- 01979999711

www.munshiganjit.com.bd   e-mail-info@munshiganjit.com.bd

HOME DELIVERY অনলাইনে অর্ডার করতে ভিজিট করুন www.munshiganjit.com.bd

OUR SHOP TECH BD21 Shop No-39, Level-4, Kassaf Shopping Center,Chittagong Road, Siddhirganj, Narayanganj

29 DIT plot, Balur mat, 4th floor, Razzak villa, Chashara, Narayanganj

MIT Care 194, Banghabandhu Road, Shomobay New Market (2nd Floor)

System

Playback Function	Instant playback, general playback, event playback, tag playback, smart playback (face and motion detection)
Backup Mode	USB device and network

Network

Ethernet Port	1 (10/100/1000 Mbps Ethernet port, RJ-45)

Storage

Internal HDD	2 SATA ports, up to 16TB capacity for each disk. The maximum HDD capacity varies with environment temperature.

Auxiliary Interface

USB	2 (1 front USB 2.0 port, 1 rear USB 3.0 port)
RS485	1 port, for PTZ control

Power

Power Supply	DC 12V, 5A
Power Consumption	<16 W (without HDD)

Component Environment

Operational Conditions	−10 °C to +55 °C (14 °F to +131 °F)

Construction

Dimensions	375.0 mm × 289.4 mm × 53.0 mm (14.76'' × 11.40'' × 2.09'') (W × D × H)
Net Weight	1.90 kg (4.20 lb)
Gross Weight	3.20 kg (7.00 lb)

Warranty

Manufacturing Warranty	1 year