

EZVIZ CS-H90 Dual 4MP 2K+ Dome WiFi IP Camera

Sale Price: 7800.0



PRODUCT ID: 10095

General Information	
Image Sensor	1/3" Progressive Scan CMOS
Effective Pixels	4MP+4MP
Max. Resolution	2K+ (2560 × 1440)
Frame Rate	Self-adaptive during network transmission
Lens	Top Lens: 2.8mm @ F1.6, Field of view : Diagonal 110°, Horizontal 96°, Vertical 54° Bottom Lens: 6mm @ F1.6, Field of view : Diagonal 60°, Horizontal 52°, Vertical 28°
Pan & Tilt	Top Lens: Pan: 220°, Tilt: 10° (manual adjustment for vertical angle) Bottom Lens: Pan: 324°, Tilt: 90°
IR Distance	30 m (98 ft)
Field of View	Diagonal 110°, Horizontal 96°, Vertical 54°
Min. Illumination	0.5 Lux @(F1.6, AGC ON), 0 Lux with IR (*data is obtained from EZVIZ laboratories)
Video Compression	H.265 / H.264
Bit Rate	Quad HD; Full HD; Standard adaptive bit rate
DNR	3D DNR
WDR	Digital WDR
Smart Alarm	Motion Detection, Human Detection, Human Tracking, Noise Detection, Auto Patrol
Button	Reset Button
Storage Type	Micro SD card slot (Max. 512GB)
Others	Weatherproof Design Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark
Network & Connectivity	

Wireless Network	<p>Wi-Fi Standard-IEEE802.11b, 802.11g, 802.11n Frequency Range-2.4 GHz ~ 2.4835 GHz Channel Bandwidth-Supports 20MHz Security-WPA-PSK/WPA2-PSK Transmission Rate-11b 11 Mbps, 11g 54 Mbps, 11n: 150 Mbps Wi-Fi Pairing-AP pairing Protocol EZVIZ-cloud proprietary protocol Interface Protocol-EZVIZ cloud proprietary protocol</p>
Wired Network	RJ45 × 1 (10M / 100M Adaptive Ethernet Port)
Power	
Power Supply	IP65 + 2h rainstorm
Power Consumption	MAX. 18W
Physical Specification	
Color	White
Dimension	224 × 135 × 136 mm (8.82 × 5.31 × 5.35 inch)
Weight	1203 g (42.43 oz)
Operating Temperature	-30°C to 50°C (-22 °F to 122 °F)
Others	Humidity 95% or less (non-condensing)
Warranty Information	
Warranty	01 Year Warranty