ASUS Prime B450M-A II AM4 Micro-ATX AMD Motherboard

Sale Price: 12500.0

PRODUCT ID: 00606

Basic Information

Supported CPU	AMD AM4 Socket for 3rd/ 2nd/ 1st Gen AMD Ryzen/ 2nd and 1st Gen AMD Ryzen with Radeon Vega Graphics/Athlon with Radeon Vega Graphics Processors
Chipset	AMD B450
BIOS	256 Mb Flash ROM, UEFI AMI BIOS
Form Factor	9.6 inch x 9.5 inch (24.4 cm x 24 cm)

Expansion Slots

PCI	3rd/2nd/1st Gen AMD Ryzen Processors 1 x PCIe 3.0 x16 (x16 mode) 2nd and 1st Gen AMD Ryzen with Radeon Vega Graphics Processors 1 x PCIe 3.0 x16 (x8 mode) AMD Athlon with Radeon Vega Graphics Processors 1 x PCIe 3.0 x16 (x4 mode) AMD B450 chipset 2 x PCIe 2.0 x1
M.2 Socket	Total supports 1 x M.2 slot(s):> 3rd/2nd/1st Gen AMD Ryzen/ 2nd and 1st Gen AMD Ryzen with Radeon Vega Graphics : 1 x M.2 Socket 3, with M key, type 2242/ 2260/ 2280/ 22110 storage devices support (SATA & PCIE 3.0 x 4 mode) Athlon with Radeon Vega Graphics Processors : 1 x M.2 Socket 3, with M key, type 2242/ 2260/ 2280/ 22110 storage devices support (SATA mode)

Memory

Type	Dual Channel DDR4 Memory Technology
Slots	4 x DIMM

MUNSHIGANJ IT

We Connect Whole Narayanganj...

Hotline-09614-502244

Sales-01979490143, Corporate- 01979999722
MITCare- 01979490145, Warranty-01979490146
CCTV-01979490147, Web team- 01979999711

Genuine Product | Genuine Price | Genuine Service | Genuine Care

194, Banghabandhu Road, Shomobay New Market (2nd Floor)
Shop No- 117,118,103 & 104, Level-2, Somobay New Market,
Chasara, Narayanganj-1400, Bangladesh
www.munshiganjit.com.bd   e-mail-info@munshiganjit.com.bd

HOME অনলাইনে অর্ডার করতে ভিজিট করুন
DELIVERY www.munshiganjit.com.bd

OUR SHOP   TECH BD21   Shop No- 16, 3rt Floor, Central Plaza, Signboard, Narayanganj   193, President Road, Siraj Mansion (4th Floor), Chasara, Narayanganj   MIT Care   193, President Road, Siraj Mansion (4th Floor), Chasara, Narayanganj

e-CAB   odoo

Basic Information

Supported Memory	4400(O.C)/ 4000(O.C.)/ 3866(O.C.)/ 3733(O.C.)/ 3600(O.C.)/ 3466(O.C.)/ 3400(O.C.)/ 3300(O.C.)/ 3200(O.C.)/ 3000(O.C.)/ 2800(O.C.)/ 2666/ 2400/ 2133 MHz Un-buffered Memory
Maximum Memory	128 GB

Graphics

Graphics	Integrated Graphics in the 2nd and 1st Gen AMD Ryzen with Radeon Vega Graphics/ Athlon with Radeon Vega Graphics Processors 1 x D-Sub 1 x DVI-D 1 x HDMI 2.0b

Connector & Ports

HDMI	1 x HDMI 2.0b
D-Sub (s)	1 x D-Sub
DVI-D (s)	1 x DVI-D
USB (s)	Rear USB Port (Total 6) 2 x USB 3.2 Gen 2 (up to 10Gbps) port(s)(2 x Type-A) 4 x USB 3.2 Gen 1 port(s)(4 x Type-A) Front USB Port (Total 6) 2 x USB 3.2 Gen 1 port(s) 4 x USB 2.0 port(s)
LAN Port (s)	Realtek RTL8111H ASUS LANGuard
Supported Storage	Total supports 1 x M.2 slot(s) and 6 x SATA 6Gb/s ports 3rd/2nd/1st Gen AMD Ryzen / 2nd and 1st Gen AMD Ryzen with Radeon Vega Graphics : 1 x M.2 Socket 3, with M key, type 2242/2260/2280/22110 storage devices support (SATA & PCIE 3.0 x 4 mode) Athlon with Radeon Vega Graphics Processors : 1 x M.2 Socket 3, with M key, type 2242/2260/2280/22110 storage devices support (SATA mode) 3rd/2nd/1st Gen AMD Ryzen/ 2nd and 1st Gen AMD Ryzen with Radeon Vega Graphics/ Athlon with Radeon Vega Graphics Processors : 2 x SATA 6Gb/s port(s), Support Raid 0, 1, 10 AMD B450 chipset : 4 x SATA 6Gb/s port(s), Support Raid 0, 1, 10

Basic Information

Audio	Realtek ALC887/897 7.1-Channel High Definition Audio CODEC - Supports : Jack-detection, Multi-streaming, Front Panel Jack-retasking, up to 24-Bit/192kHz playback Audio Feature : - LED-illuminated design - Audio Shielding - Dedicated audio PCB layers - Premium Japanese audio capacitors
Internal I/O Ports	1 x CPU Fan connector(s) (1 x 4 -pin) 2 x Chassis Fan connector(s) (2 x 4 -pin) 1 x USB 3.2 Gen 1(up to 5Gbps) connector(s) support(s) additional 2 USB 3.2 Gen 1 port(s) (19-pin) 2 x USB 2.0 connector(s) support(s) additional 4 USB 2.0 port(s) 1 x M.2 Socket 3 with M key, type 2242/2260/2280/22110 storage devices support (SATA & PCIE 3.0 x 4 mode) 1 x COM port(s) connector(s) 6 x SATA 6Gb/s connector(s) 1 x S/PDIF out header(s) 1 x 24-pin EATX Power connector(s) 1 x 8-pin ATX 12V Power connector(s) 1 x Front panel audio connector(s) (AAFP) 1 x System panel(s) 1 x Clear CMOS jumper(s) 1 x COM port header 1 x Speaker connector 1 x RGB Header
TPM (Trusted Platform Module)	1 x SPI TPM header

Warranty Information

Manufacturing Warranty	03 years