

GIGABYTE GA-H110M-DS2 Micro ATX Motherboard

Sale Price: 11000.0



PRODUCT ID: 02610

Basic

Information

Supported CPU	Support for 7th/6th Generation Intel® Core™ i7 processors/Intel® Core™ i5 processors/Intel® Core™ i3 processors/Intel® Pentium® processors/Intel® Celeron® processors in the LGA1151 package * For 7th Generation Intel® Core™ processors support need to update the latest BIOS. L3 cache varies with CPU
Chipset	Intel® H110 Express Chipset
BIOS	2 x 64 Mbit flash Use of licensed AMI UEFI BIOS Support for DualBIOS™ PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Form Factor	Micro ATX Form Factor; 22.6cm x 17.4cm

Expansion

Slots

PCI	1 x PCI Express x16 slot, running at x16 (The PCI Express x16 slot conforms to PCI Express 3.0 standard.) 2 x PCI Express x1 slots (The PCI Express x1 slots conform to PCI Express 2.0 standard.)
-----	---

Memory

Type	Dual channel DDR4 memory architecture
Slots	2 x DIMM
Supported Memory	Support for DDR4 2400/2133 MHz memory modules Support for ECC UDIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode) Support for non-ECC UDIMM 1Rx8/2Rx8/1Rx16 memory modules
Maximum Memory	32 GB

Basic Information

Graphics

Graphics 1 x D-Sub port, supporting a maximum resolution of 1920x1200@60 Hz

Max Shared Memory 1024 MB

Connector & Ports

HDMI 1 x HDMI

D-Sub (s) 1 x D-Sub

USB (s) Chipset:
4 x USB 3.0/2.0 ports (2 ports on the back panel, 2 ports available through the internal USB header)
6 x USB 2.0/1.1 ports (2 ports on the back panel, 4 ports available through the internal USB headers)

LAN Port (s) Realtek® GbE LAN chip (10/100/1000 Mbit)

Supported Storage 4 x SATA 6Gb/s connectors

Audio Realtek® ALC887 codec
High Definition Audio
2/4/5.1/7.1-channel
* To configure 7.1-channel audio, you have to use an HD front panel audio module and enable the multi-channel audio feature through the audio driver.
Support for S/PDIF Out

Internal I/O Ports 1 x 24-pin ATX main power connector
1 x 4-pin ATX 12V power connector
4 x SATA 6Gb/s connectors
1 x CPU fan header
1 x system fan header
1 x front panel header
1 x front panel audio header
1 x S/PDIF Out header
1 x USB 3.0/2.0 header
2 x USB 2.0/1.1 headers
1 x Clear CMOS jumper

TPM (Trusted Platform Module) 1 x Trusted Platform Module (TPM) header

Warranty Information

Basic Information

Manufacturing
Warranty 03 Years