MUNSHIGANJ IT
We Connect Whole Narayanganj...

Genuine Product | Genuine Price | Genuine Service | Genuine Care

194, Banghabandhu Road, Shomobay New Market (2nd Floor)
Shop No- 117,118,103 & 104, Level-2, Somobay New Market,
Chasara, Narayanganj-1400, Bangladesh
www.munshiganjit.com.bd   e-mail-info@munshiganjit.com.bd

Hotline-09614-502244
Sales-01979490143, Corporate- 01979999722
MITCare- 01979490145, Warranty-01979490146
CCTV-01979490147, Web team- 01979999711

HOME DELIVERY
অনলাইনে অর্ডার করতে ভিজিট করুন
www.munshiganjit.com.bd

OUR SHOP TECH BD21 Shop No- 16, 3rt Floor, Central Plaza, Signboard, Narayanganj

193, President Road, Siraj Mansion (4th Floor), Chasara, Narayanganj

MIT Care 193, President Road, Siraj Mansion (4th Floor), Chasara, Narayanganj

GIGABYTE GA-H110M-H Micro ATX Motherboard

Sale Price: 11500.0

PRODUCT ID: 02611

Basic Information

Supported CPU	Support for 7th/6th Generation Intel® Core™ i7 processors/Intel® Core™ i5 processors/Intel® Core™ i3 processors/Intel® Pentium® processors/Intel® Celeron® processors in the LGA1151 package * For 7th Generation Intel® Core™ processors support need to update the latest BIOS. L3 cache varies with CPU
Chipset	Intel® H110 Express Chipset
BIOS	1 x 64 Mbit flash Use of licensed AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Form Factor	Micro ATX Form Factor; 22.6cm x 17.4cm

Expansion Slots

PCI	1 x PCI Express x16 slot, running at x16 (The PCI Express x16 slot conform to PCI Express 3.0 standard.) 2 x PCI Express x1 slots (All of the PCI Express x1 slots conform to PCI Express 2.0 standard.)

Memory

Type	Dual channel DDR4 memory architecture
Slots	2 x DIMM
Supported Memory	Support for DDR4 2400/2133 MHz memory modules Support for ECC UDIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode) Support for non-ECC UDIMM 1Rx8/2Rx8/1Rx16 memory modules
Maximum Memory	32 GB

Graphics

Basic Information

Graphics	1 x D-Sub port, supporting a maximum resolution of 1920x1200@60 Hz 1 x HDMI port, supporting a maximum resolution of 4096x2160@24 Hz * Support for HDMI 1.4 version.
Max Shared Memory	1024 MB

Connector & Ports

HDMI	1 x HDMI
D-Sub (s)	1 x D-Sub
USB (s)	Chipset: 4 x USB 3.0/2.0 ports (2 ports on the back panel, 2 ports available through the internal USB header) 6 x USB 2.0/1.1 ports (2 ports on the back panel, 4 ports available through the internal USB headers)
LAN Port (s)	Realtek® GbE LAN chip (10/100/1000 Mbit)
Supported Storage	Chipset: 4 x SATA 6Gb/s connectors
Audio	Realtek® ALC887 codec High Definition Audio 2/4/5.1/7.1-channel * To configure 7.1-channel audio, you have to use an HD front panel audio module and enable the multi-channel audio feature through the audio driver. Support for S/PDIF Out
Internal I/O Ports	1 x 24-pin ATX main power connector 1 x 4-pin ATX 12V power connector 4 x SATA 6Gb/s connectors 1 x CPU fan header 1 x system fan header 1 x front panel header 1 x front panel audio header 1 x S/PDIF Out header 1 x USB 3.0/2.0 header 2 x USB 2.0/1.1 headers 1 x Clear CMOS jumper
TPM (Trusted Platform Module)	1 x Trusted Platform Module (TPM) header

Warranty Information

Basic Information

Manufacturing Warranty	03 Years