

GIGABYTE H510M S2H Intel 10th and 11th Gen Micro ATX Motherboard

Sale Price: 10500.0



PRODUCT ID: 02660

Basic

Information

Supported CPU	11th Generation Intel Core i9 processors / Intel Core i7 processors / Intel Core i5 processors 10th Generation Intel Core i9 processors / Intel Core i7 processors / Intel Core i5 processors / Intel Core i3 processors / Intel Pentium processors / Intel Celeron processors * Limited to processors with 4 MB Intel Smart Cache, Intel Celeron G5xx5 family.
Chipset	Intel H510 Express Chipset
BIOS	1 x 256 Mbit flash Use of licensed AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Form Factor	Micro ATX Form Factor; 24.4cm x 21.0cm
Audio	Realtek Audio CODEC High Definition Audio 2/4/5.1/7.1-channel

Expansion

Slots

PCI	1 x PCI Express x16 slot, running at x16 (The PCI Express x16 slot conforms to PCI Express 4.0 standard.) * Supported by 11th Generation processors only. 2 x PCI Express x1 slots (The PCI Express x1 slots conform to PCI Express 3.0 standard.)
M.2 Socket	1 x M.2 connector (Socket 3, M key, type 2260/2280 SATA and PCIe 3.0 x4/x2 SSD support)

Memory

Type	Dual channel memory architecture
Slots	2 x DDR4 DIMM

Basic Information

Supported Memory	11th Generation Intel Core i9/i7/i5 processors: Support for DDR4 3200/3000/2933/2666/2400/2133 MHz memory modules 10th Generation Intel Core i9/i7 processors: Support for DDR4 2933/2666/2400/2133 MHz memory modules 10th Generation Intel Core i5/i3/Pentium/Celeron processors: Support for DDR4 2666/2400/2133 MHz memory modules 2 x DDR4 DIMM sockets supporting up to 64 GB (32 GB single DIMM capacity) of system memory Dual channel memory architecture Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode) Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules Support for Extreme Memory Profile (XMP) memory modules
Maximum Memory	64 GB (32 GB single DIMM capacity)

Graphics

Graphics	Integrated Graphics Processor-Intel HD Graphics support: 1 x D-Sub port, supporting a maximum resolution of 1920x1200@60 Hz * When the D-Sub port and DisplayPort are connected at the same time, images will output from the DisplayPort only. 1 x DVI-D port, supporting a maximum resolution of 1920x1200@60 Hz * The DVI-D port does not support D-Sub connection by adapter. 1 x HDMI ports, supporting a maximum resolution of 4096x2160@30 Hz * Support for HDMI 1.4 version and HDCP 2.3. 1 x DisplayPort, supporting a maximum resolution of 4096x2304@60 Hz * Support for DisplayPort 1.2 version and HDCP 2.3 * When the D-Sub port and DisplayPort are connected at the same time, images will output from the DisplayPort only. Support for up to 2 displays at the same time
----------	--

Connector & Ports

HDMI	1 x HDMI ports, supporting a maximum resolution of 4096x2160@30 Hz
Display Port (s)	1 x DisplayPort, supporting a maximum resolution of 4096x2304@60 Hz
D-Sub (s)	1 x D-Sub port
DVI-D (s)	1 x DVI-D port
USB (s)	Chipset: 4 x USB 3.2 Gen 1 ports (2 ports on the back panel, 2 ports available through the internal USB header) Chipset+USB 2.0 Hub: 8 x USB 2.0/1.1 ports (4 ports on the back panel, 4 ports available through the internal USB header)
LAN Port (s)	Realtek GbE LAN chip (1 Gbit/100 Mbit)

Basic Information

Supported Storage	1 x M.2 connector (Socket 3, M key, type 2260/2280 SATA and PCIe 3.0 x4/x2 SSD support) * The PCIe1_1 slot shares bandwidth with the M.2 connector. When the PCIe1_1 slot is populated, the M.2 connector supports up to PCIe 3.0 x2 SSD only. 4 x SATA 6Gb/s connectors
Audio	3 x audio jacks
Internal I/O Ports	1 x 24-pin ATX main power connector 1 x 8-pin ATX 12V power connector 4 x SATA 6Gb/s connectors 1 x CPU fan header 2 x system fan headers 1 x RGB LED strip header 1 x front panel header 1 x front panel audio header 1 x speaker header 1 x USB 3.2 Gen 1 header 2 x USB 2.0/1.1 headers 1 x serial port header 1 x Clear CMOS jumper
TPM (Trusted Platform Module)	1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module only)

Others

Special Features	Support for APP Center @BIOS Ambient LED EasyTune Fast Boot Game Boost ON/OFF Charge Smart Backup System Information Viewer Support for Q-Flash Support for Xpress Install
Bundled Software	Norton Internet Security (OEM version) Realtek 8118 Gaming LAN Bandwidth Control Utility

Warranty Information

Manufacturing Warranty	3 years
------------------------	---------



MUNSHIGANJ IT

We Connect Whole Narayanganj...

A Super Store Of Computer & Electronics Accessoriess

194, Banghabandhu Road, Shomobay New Market (2nd Floor)

Shop No. 117-118,103-104, Chasara, Narayanganj-1400

www.munshiganjit.com.bd e-mail-info@munshiganjit.com.bd

Hotline-09614-502244

Sales-01979490143, Corporate- 01979999722

MITCare- 01979490145, Warranty-01979490146

CCTV-01979490147, Web team- 01979999711

OUR SHOP **TECH BD21**

Shop No-39, Level-4, Kassaf
Shopping Center,Chittagong Road,
Siddhirganj, Narayanganj



29 DIT plot, Balur mat,
4th floor, Razzak villa,
Chashara, Narayanganj



194, Banghabandhu Road,
Shomobay New Market
(2nd Floor)



50/-
Delivery Charge
Inside Narayanganj City

**HOME
DELIVERY**

অনলাইনে অর্ডার করতে ভিজিট করুন
www.munshiganjit.com.bd

