

## GIGABYTE B760M H DDR4 mATX Motherboard

Sale Price: 1.0



PRODUCT ID: 02593

### Basic Information

Supported CPU	LGA1700 socket: Support for the 14th, 14th and 12th Generation Intel Core, Pentium Gold and Celeron Processors L3 cache varies with the CPU
Chipset	Intel B760 Express Chipset
BIOS	1 x 128 Mbit flash Use of licensed AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Form Factor	Micro ATX Form Factor; 23.0cm x 21.5cm
Audio	Realtek Audio CODEC High Definition Audio 2/4/5.1/7.1-channel * You can change the functionality of an audio jack using the audio software. To configure 7.1-channel audio, access the audio software for audio settings. Support for S/PDIF Out

### Expansion Slots

PCI	CPU: - 1 x PCI Express x16 slot, supporting PCIe 4.0 and running at x16 Chipset: - 1 x PCI Express x1 slot, supporting PCIe 3.0 and running at x1
-----	--

### Memory

Type	DDR4
Slots	2

## Basic Information

Supported Memory	Support for DDR4 3200/3000/2933/2666/2400/2133 MT/s memory modules Dual channel memory architecture Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode) Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules Support for Extreme Memory Profile (XMP) memory modules
Maximum Memory	up to 64GB (32 GB single DIMM capacity) of system memory

## Graphics

Graphics	Integrated Graphics Processor-Intel HD Graphics support: - 1 x D-Sub port, supporting a maximum resolution of 1920x1200@60 Hz - 1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz * Support for HDMI 2.0 version and HDCP 2.3.
----------	---

## Connector & Ports

HDMI	1x HDMI
D-Sub (s)	1x D-Sub
USB (s)	Chipset: - 6 x USB 3.2 Gen 1 ports (4 ports on the back panel, 2 ports available through the internal USB header) - 6 x USB 2.0/1.1 ports (2 ports on the back panel, 4 ports available through the internal USB headers)
LAN Port (s)	Realtek GbE LAN chip (1 Gbps/100 Mbps)
Supported Storage	CPU: - 1 x M.2 connector (Socket 3, M key, type 2280 PCIe 4.0 x4/x2 SSD support) (M2A_CPU) Chipset: - 1 x M.2 connector (Socket 3, M key, type 2280 PCIe 4.0 x4/x2 SSD support) (M2P_SB) - 4 x SATA 6Gb/s connectors
RAID	RAID 0, RAID 1, RAID 5, and RAID 10 support for SATA storage devices
Audio	3 x audio jacks

## Basic Information

Internal I/O Ports	1 x 24-pin ATX main power connector 1 x 8-pin ATX 12V power connector 1 x CPU fan header 2 x system fan headers 1 x RGB LED strip header 2 x M.2 Socket 3 connectors 4 x SATA 6Gb/s connectors 1 x front panel header 1 x front panel audio header 1 x S/PDIF Out header 1 x USB 3.2 Gen 1 header 2 x USB 2.0/1.1 headers 1 x serial port header 1 x Clear CMOS jumper
TPM (Trusted Platform Module )	1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module only)

## Others

Special Features	Support for GIGABYTE Control Center (GCC) Support for Q-Flash
Bundled Software	Norton Internet Security (OEM version) LAN bandwidth management software

## Warranty Information

Manufacturing Warranty	3 years
------------------------	---------