



Hikvision 2MP Bullet Network Camera 20 MTR Distance, Lens 6.00 MM #DS-2CD2T25FWD-I5

Sale Price: 9000.0

PRODUCT ID: 03477

General

Dimensions	Φ105 × 299.7 mm (Φ4.13" × 11.80")
Weight	1200 g (2.65 lb.)
Pan/Tilt/Rotation	Pan: 0° to 360°, tilt: 0° to 100°, rotate 0° to 360°
Operating Conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F) Humidity 95% or less (non-condensing)
Power Supply	12 VDC ± 25%, PoE (802.3af Class3)
Power Consumption	-I5: 12 VDC ± 25%, 7 W; PoE, 9 W -I8: 12 VDC ± 25%, 10 W; PoE, 12.5 W

Camera

Image Sensor	1/2.8" Progressive Scan CMOS
Scanning System	PAL/NTSC
Electronic Shutter Speed	1/3 s to 1/100,000 s
Minimum Illumination	Color: 0.005 Lux @ (F1.2, AGC ON), 0 Lux with IR Color: 0.009 Lux @ (F1.6, AGC ON), 0 Lux with IR
IR Distance	IR range: 50m, 80m, optional

Lens

Lens Type	2.8 mm, horizontal field of view: 108° 4 mm, horizontal field of view: 86.4° 6 mm, horizontal field of view: 52° 8 mm, horizontal field of view: 41° 12 mm, horizontal field of view: 25°
Mount Type	M12
Focal Length	Fixed

General

Video

Resolution	1920 x 1080
Frame Rate	50Hz: 25fps (1920 × 1080, 1280 × 960, 1280×720) 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280×720)
Day/Night	IR cut filter with auto switch
BLC Mode	BLC/3D DNR/BLC
Noise Reduction	3D Digital Noise Reduction

Warranty

Warranty	1 year
----------	--------