



Hikvision 04 Channel NVR (1 SATA UP to 6TB) 1080P, H.265+/H2.65+, UP TO 8MP Network Camera Supports#DS-7604NI-K1

Sale Price: 6500.0

PRODUCT ID: 03455

— System

| | |
|------------------|---|
| Main Processor | Dual-core embedded processor |
| Operating System | Dual-OS design to ensure high reliability of system running |

Audio and Video

| | |
|-----------------|--|
| IP Camera Input | 4 Channel |
| Two-Way Talk | 1 Channel Input, 1 Channel Output, RCA |

Display

| | |
|----------------------|---|
| Interface | 1 HDMI, 1 VGA |
| Resolution | HDMI: 1920×1080, 1280×1024, 1280×720, 1024×768 VGA: 1920×1080, 1280×1024, 1280×720, 1024×768 |
| Decoding Capacity | 4-ch @ 1080p |
| Multi-Screen Display | 2 |

Recording

| | |
|-------------|---|
| Compression | H.265/H.264/H.264+ |
| Resolution | 8MP/6MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF |
| Record Rate | 40Mbps |

Video Detection And Alarm

| | |
|-------------|-----|
| Alarm Input | Yes |
|-------------|-----|

Playback And Backup

| | |
|-------------------|----------------------------------|
| Playback Function | live view, storage, and playback |
| Backup Mode | USB Device/Network |



System

Network

| | |
|-------------------------|---|
| Interface | 1 RJ-45 10 M/100 Mbps self-adaptive Ethernet interface face 2 x USB 2.0 |
| Ethernet Port | 1 RJ-45 10 M/100 Mbps self-adaptive Ethernet interface |
| PoE | N/A |
| Network Function | TCP/IP, DHCP, HIK Cloud P2P, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS |
| Optical Fiber Interface | N/A |

Storage

| | |
|--------------|--|
| Internal HDD | 1 SATA interface for 1HDD Capacity Up to 6TB capacity for each disk |
| HDD Mode | Single |
| eSATA | 1 SATA interface connectable for recording and backup |

Auxiliary Interface

| | |
|-------|-------------|
| USB | 2 x USB 2.0 |
| RS232 | N/A |
| RS485 | N/A |

Power

| | |
|-------------------|--------|
| Power Supply | 12 VDC |
| Power Consumption | ≤ 10 W |

Component Environment

| | |
|------------------------|--|
| Operational Conditions | -10 to +55° C (14 to 131° F) Working humidity: 10 to 90 % |
|------------------------|--|

Construction

| | |
|--------------|---|
| Dimensions | 260 x 225 x 48 mm (10.2" x 8.9" x 1.9") |
| Gross Weight | ≤ 1 kg (2.2 lb) |