

Hikvision 16 Channel NVR (1 Sata UP to 16TB) 1080P, H.265+/H.2.65+, UP TO 8MP Network Camera Supports#DS-7616NI-Q1



Sale Price: 10500.0

PRODUCT ID: 03470

— Audio and Video

IP Camera Input	Up to 16 IP cameras can be connected HDMI/VGA simultaneous output (DS-7604NI-Q1)
Two-Way Talk	1-ch, RCA (2.0 Vp-p, 1 k Ω)

Display

Interface	HDMI and VGA independent outputs (DS-7608NI-Q1 and DS-7616NI-Q1)
Resolution	HDMI output resolution : 1-ch, 4K (3840 × 2160)/30Hz, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz VGA output resolution : 1-ch, 1920 × 1080p/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Decoding Capacity	1-ch @ 8 MP / 4-ch @ 1080p/8-ch @ 1080p

Recording

Compression	H.265+/H.265/H.264/H.264+
Resolution	8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF
Record Rate	160 Mbps

Video Detection And Alarm

Alarm Input	4/1 (optional)
-------------	----------------

Playback And Backup

Sync Playback	Yes (16-ch)H.265+/H.265/H.264/H.264+
Playback Function	live view, storage, and playback
Backup Mode	USB Device/Network

Audio and Video

Third Party Support

Third Party Support	Yes
---------------------	-----

Network

Interface	1, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
Ethernet Port	1
Network Function	TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP, HTTPS

Storage

HDD Mode	1 SATA interface Up to 6TB capacity for each disk
----------	--

Auxiliary Interface

USB	2 × USB 2.0
-----	-------------

Power

Power Supply	12 VDC
Power Consumption	Power : ≤ 18W Consumption (without hard disk) : ≤ 10 W

Construction

Dimensions	315 × 240 × 48 mm (12.4" × 9.4" × 1.9")
Net Weight	disk) ≤ 1 kg (2.2 lb)