

## Hikvision 64 Channel 4HDD 8K NVR (8 Sata UP to 80TB) 1080P, H.265+/H2.65+, UP TO 32MP Network Camera Supports#DS-7764NI-M4



Sale Price: 50000.0

PRODUCT ID: 03514

### Audio and Video

IP Camera Input	64-ch Up to 32 MP resolution * After ultra HD resolution mode is enabled, the NVR supports up to 8-ch 32 MP/24 MP IP video inputs.
Two-Way Talk	1-ch, RCA (2.0 Vp-p, 1 KΩ, using the audio input)

### Display

Interface	HDMI1/VGA simultaneous output, HDMI1/HDMI2 independent output
Resolution	HDMI 1: Output 8K (7680 × 4320)/30Hz, 4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz HDMI 2: Output 4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz *: When HDMI 1 output resolution is 8K, the maximum HDMI 2 output resolution is 1080p. VGA: Output 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Decoding Capacity	2-ch@32 MP (30 fps)/2-ch@24 MP (30 fps)/4-ch@12 MP (20 fps)/8-ch@8 MP (25 fps)/16-ch@4 MP (30 fps)/32-ch@1080p (30 fps)

### Recording

Compression	Audio Compression G.711ulaw/G.711alaw/G.722/G.726/AAC/MP2L2
Resolution	32 MP/24 MP/12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA /4CIF/DCIF/ 2CIF/CIF/QCIF *After ultra HD resolution mode is enabled, the NVR supports up to 8-ch 32 MP/24 MP IP video inputs.

### Video Detection And Alarm

Alarm Input	16/9
-------------	------

## Audio and Video

### Playback And Backup

Sync Playback 16-ch

## Network

Interface ESATA: 1x eSATA interface  
 SATA: 4x SATA interfaces  
 Capacity: Up to 16 TB capacity for each HDD  
 Serial Interface: 2x RS-485 (half-duplex), 1 RS-232  
 Alarm In/Out: 16/9  
 USB Interface: Front panel: 2 × USB 2.0; Rear panel: 1 × USB 3.0  
 Ctrl 12V: Controllable 12 VDC, 1 A power output for external alarm device; The power will be turned on when the alarm output is triggered.  
 \*The Ctrl 12V power is controlled by alarm output 9.  
 DC 12V: 12 VDC, 1 A power output

Ethernet Port 2x RJ-45 10/100/1000 Mbps self-adaptive Ethernet interfaces

## Storage

Internal HDD Up to 16 TB capacity for each HDD

eSATA Yes

## Auxiliary Interface

USB Front panel: 2 × USB 2.0  
 Rear panel: 1 × USB 3.0

## Power

Power Supply 100 to 240 VAC, 50 to 60 Hz

Power Consumption ≤ 15 W (without HDD)

## Component Environment

Operational Conditions -10 °C to 55 °C (14 °F to 131 °F)

## Construction

Dimensions 445 × 400 × 75 mm ( 17.5"× 15.7" × 3.0")

## Audio and Video

Net Weight ≤ 5 kg (without HDD, 11 lb.)

## Warranty

Manufacturing Warranty 1 Year