

## Cudy GS1006P 4-GbE PoE Switch with 2 Uplink GbE

Regular Price: 5900.0

Sale Price: 5000.0



PRODUCT ID: 01469

Networking & Connectivity

Switching Capacity

802.3 Protocols:

802.3i 10BASE-T

802.3u 100BASE-T

802.3ab 1000BASE-T

802.3x Flow Control

802.3af PoE

802.3at PoE

Port Management: Watchdog

Port Management Note: The Watchdog is on under the VLAN/

Extend modes and will attempt to reboot the plugged-in but inactive client.

Battery And Power

Power

Power Methods: AC

AC: 100-240V 50/60Hz

Max Power Consumption: 65W

Max Power Excluding PoE: 5W

Ports

Interface

Physical Buttons: VLAN/Default/Extend DIP Switch

Gigabit RJ45 Ports: 2

Gigabit RJ45 PoE Ports: 4

Max Power on a Single PoE Port: 30W

PoE Port Notes: PoE ports support 802.3at/af standards.

Extend Mode Ports: #3~#4

VLAN Mode Ports: #1~#4

LED: Power, DIP Mode (SW), Link/ACT of Each Ethernet Port

Power Input: AC Inlet

Others

Included in the Box

GS1006P

Power Cord

Installation Guide

Technical Info

Installation

Desktop, Rackmount via Brackets

Performance

Copper Speed and Distance:

Cat. 3 or higher cable: 100 meters at 10 Mbps

Cat. 5 or higher cable: 100 meters at 100 Mbps

Cat. 5e or higher cable: 100 meters at Gigabit

Cat. 5e or higher cable: 250 meters at 10 Mbps

Model

GS1006P

Warranty Information

Warranty

1 years