

Tp-Link EAP620 HD AX1800 Ceiling Mount WiFi 6 Access Point



Regular Price: 16000.0

Sale Price: 14900.0

PRODUCT ID: 06133

— Main Feature

Antenna	Internal Omni Antenna <ul style="list-style-type: none">• 2.4 GHz: 2× 4 dBi• 5 GHz: 2× 5 dBi
Button	Reset
Temperature	<ul style="list-style-type: none">• Operating Temperature: 0–40 °C (32–104 °F)• Storage Temperature: -40–70 °C (-40–158 °F)
Dimensions	6.3 × 6.3 × 1.3 in (160 × 160 × 33.6 mm)

Power

DC jack input Voltage	12 V / 1.5 A DC
Number of DC inputs	1
PoE in	IEEE802.3at PoE and Passive PoE
PoE in input Voltage	48 V Passive PoE
Power consumption	<ul style="list-style-type: none">• EU: 14.4 W (For PoE); 13.1 W (for DC)• US: 14.9 W (For PoE); 13.4 W (for DC)

Network

Wireless Rate	<ul style="list-style-type: none">• 5 GHz: Up to 1201 Mbps• 2.4 GHz: Up to 574 Mbps
Wireless frequency	2.4 GHz and 5 GHz
Wireless standards	IEEE 802.11ax/ac/n/g/b/a
Ethernet	1× Gigabit Ethernet (RJ-45) Port (supports IEEE802.3at PoE and Passive PoE)

Main Feature

Wireless Security

- Captive Portal Authentication△
- Access Control
- Wireless Mac Address Filtering
- Wireless Isolation Between Clients
- SSID to VLAN Mapping
- Rogue AP Detection
- 802.1X Support
- WEP, WPA-Personal/Enterprise, WPA2-Personal/Enterprise, WPA3-Personal/Enterprise

Others

Wireless Functions

- 1024-QAM
- 4x Longer OFDM Symbol
- OFDMA
- Multiple SSIDs (Up to 16 SSIDs, 8 for each band)
- Enable/Disable Wireless Radio
- Automatic Channel Assignment
- Transmit Power Control (Adjust Transmit Power on dBm)
- QoS(WMM)
- MU-MIMO
- Seamless Roaming△
- Omada Mesh△
- Band Steering
- Load Balance
- Airtime Fairness
- Beamforming
- Rate Limit
- Reboot Schedule
- Wireless Schedule
- Wireless Statistics based on SSID/AP/Client

Manufacture Warranty

Warranty

06-Months Warranty