



## Tp-Link EAP610-Outdoor AX1800 Indoor Outdoor WiFi 6 Access Point

Regular Price: 15400.0

Sale Price: 14900.0

PRODUCT ID: 06132

### — Main Feature

Antenna	<ul style="list-style-type: none"><li>• 2.4 GHz: 2× 4 dBi</li><li>• 5 GHz: 2× 5 dBi</li></ul>
Button	Reset
Temperature	<ul style="list-style-type: none"><li>• Operating Temperature: -30~70 °C (-22~158 °F)</li><li>• Storage Temperature: -40~70 °C (-40~158 °F)</li></ul>
Dimensions	• 280.4×106.5×56.8 mm (without antenna & mounting kit)

### Power

PoE in	Support 802.3at PoE and Passive PoE
Power consumption	<ul style="list-style-type: none"><li>• EU: 12.5W (802.3at PoE or Passive PoE)</li><li>• US: 14.7W (802.3at PoE or Passive PoE)</li></ul>

### Network

Wireless Rate	<ul style="list-style-type: none"><li>• 802.11ax: 8 Mbps to 1201 Mbps (MCS0-MCS11, NSS = 1 to 2 HE20/40/80)</li><li>• 802.11ac: 6.5 Mbps to 867 Mbps (MCS0-MCS9, NSS = 1 to 2 VHT20/40/80)</li><li>• 802.11n: 6.5 Mbps to 300 Mbps (MCS0-MCS15, VHT 20/40)</li><li>• 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li><li>• 802.11b: 1, 2, 5.5, 11 Mbps</li><li>• 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li></ul>
Wireless frequency	2.4 GHz, 5 GHz
Wireless standards	IEEE 802.11ax/ac/n/g/b/a
Ethernet	1× Gigabit Ethernet (RJ-45) Port (Support 802.3at PoE and Passive PoE)

## Main Feature

### Wireless Security

- Captive Portal Authentication\*\*
- Access Control
- Wireless Mac Address Filtering
- Wireless Isolation Between Clients
- SSID to VLAN Mapping
- Rogue AP Detection
- 802.1X Support
- WEP, WPA-Personal/Enterprise, WPA2-Personal/Enterprise, WPA3-Personal/Enterprise

### Others

#### Wireless Functions:

- 1024-QAM
- 4x Longer OFDM Symbol
- OFDMA
- Multiple SSIDs (Up to 16 SSIDs, 8 for each band)
- Enable/Disable Wireless Radio
- Automatic Channel Assignment
- Transmit Power Control (Adjust Transmit Power on dBm)
- QoS (WMM)
- MU-MIMO
- Omada Mesh\*\*
- Seamless Roaming\*\*
- Band Steering
- Load Balance
- Airtime Fairness
- Beamforming
- Rate Limit
- Reboot Schedule
- Wireless Schedule
- Wireless Statistics based on SSID/AP/Client

## Manufacture Warranty

Warranty

2 year