

Hotline-09614-502244

Sales-01979490143, Corporate- 01979999722 MITCare- 01979490145, Warranty-01979490146 CCTV-01979490147, Web team- 01979999711


194, Banghabandhu Road, Shomobay New Market (2nd Floor) Shop No. 117-118,103-104, Chasara, Narayanganj-1400

www.munshiganjit.com.bd e-mail-info@munshiganjit.com.bd











194, Banghabandhu Road Shomobay New Market (2nd Floor)







PRODUCT ID: 04601

- Wireless N transfer speed up to 300Mbps
- High transmission power to boost wireless signal for further distance
- Provides powerful Wi-Fi coverage that easily penetrates walls obstructions and eliminates dead zones
- 802.3af&at standard PoE design for flexible deployment
- Stylish ceiling-mounted appearance for easy Installation to wall or ceiling surface
- Supports Access Point, AP Router, Client, WDS, Repeater, and WISP modes
- Zero configuration under default Access Point mode
- Quick setup, with built-in multilingual management page
- Standards IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
- Signal Rate Up to 300Mbps
- Frequency Range 2.4-2.4835GHz
- Transmit Power < 20dBm (For countries using CE Standards)
- <30dBm (For countries using FCC Standards)
- Wireless Modes Access Point, Client, WDS, AP+WDS, Client+Repeater
- Wireless Security WEP (64/128-bit), WPA-PSK, WPA2-PSK, WPA-PSK/WPA2-PSK Mixed Mode, SSID Broadcast Enable/Disable, MAC Address Filtering
- Buttons RESET
- Antenna 2* Internal Antenna
- Power Supply 802.3af&at PoE
- Interface WAN/PoE: 10/100Mbps Auto MDI/MDIX RJ45 LAN port.802.3 af & at PoE Supported,LAN: 10/100Mbps Auto MDI/MDIX RJ45 LAN port,