

Dahua DH-HAC-HFW1200THP-I8 3.6mm 2MP Bullet CC Camera

Sale Price: 2700.0



PRODUCT ID: 01881

General

Casing	Metal front cover+plastic main body, and metal bracket
Dimensions	240.7 mm × 90.7 mm × 90.4 mm (9.48" × 3.57" × 3.56")
Weight	0.41 Kg (0.90 lb)
Pan/Tilt/Rotation	Pan: 0°-360° Tilt: 0°-180° Rotation: 0°-360°
Operating Conditions	-40°C to +60°C (-40°F to 140°F); <95% (non-condensation)
Storage Conditions	-40°C to +60°C (-40°F to 140°F); <95% (non-condensation)
Power Supply	12V ±30% DC
Power Consumption	Max 4.9W (12V DC, IR on)

Camera

Image Sensor	1/2.7 inch CMOS
Effective Pixels	1920(H)×1080(V), 2MP
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/25s-1/100000s NTSC: 1/30s-1/100000s
Minimum Illumination	0.02Lux/F1.9, 30IRE, 0Lux IR on
S/N Ratio	>65dB
IR Distance	80 m (262.5 ft)
IR On/Off Control	Auto; manual
IR LEDs	2

Lens

Lens Type	Fixed-focal
-----------	-------------

General

Mount Type	M12
Focal Length	3.6 mm; 6 mm; 8 mm
Max Aperture	F1.9
Close Focus Distance	3.6 mm: 0.8 m (2.6 ft) 6 mm: 2 m (6.6 ft) 8 mm: 3.5 m (11.5 ft)

Video

Resolution	1080P (1920×1080); 720P (1280×720); 960H (960× 576/960×480)
Frame Rate	CVI: 1080P@25/30fps; 720P@25/30fps; 720P@50/60fps; AHD: 1080P@25/30fps; 720P@25/30fps; TVI: 1080P@25/30fps; 720P@25/30fps; 720P@50/60fps; CVBS: 960H
Video Output	Video output choices of CVI/TVI/AHD/CVBS by one BNC port
Day/Night	Auto switch by ICR
BLC Mode	BLC/HLC/DWDR
Gain Control	Auto; manual
Noise Reduction	2D NR

Special Features

Features	Smart IR Electronic Defog Fixed iris DWDR
----------	--

Warranty

Warranty	1-Year
----------	--------