



Dahua HAC-HDW1200TLP-A 2MP HDCVI IR Eyeball Camera with Audio

Sale Price: 2500.0

PRODUCT ID: 01914

General

Casing	Inner core: metal+plastic; cover: plastic
Dimensions	Φ97.0mm×85.8mm (Φ3.82"×3.38")
Weight	0.22 Kg
Pan/Tilt/Rotation	Pan: 0°-360° Tilt: 0°-78° Rotation: 0°-360°
Operating Conditions	-40°C to +60°C (-40°F to +140°F); <95% (non-condensation)
Storage Conditions	-40°C to +60°C (-40°F to +140°F); <95% (non-condensation)
Power Supply	12V±30% DC
Power Consumption	Max 3.6W (12V DC, IR on)

Camera

Image Sensor	1/2.7 inch CMOS
Effective Pixels	1920 (H)×1080 (V), 2MP
Electronic Shutter Speed	PAL: 1/25s-1/100000s NTSC: 1/30s-1/100000s
Minimum Illumination	0.02Lux/F1.85, 30IRE, 0Lux IR on
IR Distance	30m (98.42ft)
IR On/Off Control	Auto; manual
IR LEDs	1

Lens

Lens Type	Lens Type: Fixed-focal Iris Type: Fixed iris
Mount Type	M12

General

Focal Length	2.8mm; 3.6mm
Max Aperture	F1.85/F2.0
Angle of View	2.8mm: 118°×103°×59° (diagonal×horizontal×vertical) 3.6mm: 103.8°×87.5°×47° (diagonal×horizontal×vertical)
Close Focus Distance	0.5m (1.64ft)/0.9m (2.95ft)

Video

Resolution	1080P (1920×1080); 720P (1280×720); 960H (960× 576/960×480)
Frame Rate	CVI: PAL: 1080P@25fp; 720P@25fps; 720@50fps NTSC: 1080P@30fp; 720P@30fps; 720@60fps AHD: PAL: 1080P@25fp; 720P@25fps NTSC: 1080P@30fp; 720P@30fps TVI: PAL: 1080P@25fp; 720P@25fps; 720@50fps NTSC: 1080P@30fp; 720P@30fps; 720@60fpsCVBS: PAL: 960H NTSC: 960H
Video Output	Video output choices of CVI/TVI/AHD/CVBS by one BNC port
Day/Night	Auto switch by ICR
BLC Mode	BLC/HLC/DWDR
Gain Control	Auto; manual
Noise Reduction	2D NR

Interface

Audio Interface	Built-in mic (-A)
Video Interface	Video output choices of CVI/TVI/AHD/CVBS by one BNC port

Warranty

Warranty	1 Year
----------	--------