

GIGABYTE B760M AORUS ELITE DDR5 mATX Motherboard

Sale Price: 24500.0



PRODUCT ID: 02582

Basic Information

Supported CPU	LGA1700 socket: Support for the 14th 13th and 12th Generation Intel Core, Pentium Gold and Celeron Processors L3 cache varies with the CPU
Chipset	Intel B760 Express Chipset
BIOS	1 x 256 Mbit flash Use of licensed AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Form Factor	Micro ATX Form Factor; 24.4cm x 24.4cm
Audio	Realtek Audio CODEC High Definition Audio 2/4/5.1/7.1-channel Support for S/PDIF Out

Expansion

Slots

PCI	CPU: 1 x PCI Express x16 slot, supporting PCIe 4.0 and running at x16 (PCIEX16) Chipset: 1 x PCI Express x16 slot, supporting PCIe 4.0 and running at x4 (PCIEX4) Support for AMD CrossFireX technology
-----	---

Memory

Type	DDR5
Slots	4

Basic Information

Supported Memory	Support for DDR5 7600(O.C.) / 7400(O.C.) / 7200(O.C.) / 7000(O.C.) / 6800(O.C.) / 6600(O.C.) / 6400(O.C.) / 6200(O.C.) / 6000(O.C.) / 5800(O.C.) / 5600(O.C.) / 5400(O.C.) / 5200(O.C.) / 4800 / 4000 MT/s memory modules Dual channel memory architecture Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode) Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules Support for Extreme Memory Profile (XMP) memory modules
Maximum Memory	up to 192 GB (48 GB single DIMM capacity)

Graphics

Graphics	Integrated Graphics Processor-Intel HD Graphics support: 1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz 1 x DisplayPort, supporting a maximum resolution of 4096x2304@60 Hz
----------	--

Connector & Ports

HDMI	1x HDMI
Display Port (s)	1x DisplayPort
USB (s)	1 x USB Type-C port on the back panel, with USB 3.2 Gen 2x2 support 1 x USB Type-C port with USB 3.2 Gen 2 support, available through the internal USB header 1 x USB 3.2 Gen 2 Type-A port (red) on the back panel 1 x USB 3.2 Gen 1 port on the back panel 4 x USB 2.0/1.1 ports available through the internal USB headers Chipset+USB 3.2 Gen 1 Hub: 4 x USB 3.2 Gen 1 ports (2 ports on the back panel, 2 ports available through the internal USB header) Chipset+USB 2.0 Hub: 4 x USB 2.0/1.1 ports on the back panel
LAN Port (s)	Realtek 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps)
Supported Storage	CPU: 1 x M.2 connector (Socket 3, M key, type 2280 PCIe 4.0 x4/x2 SSD support) (M2A_CPU) Chipset: 1 x M.2 connector (Socket 3, M key, type 22110/2280 PCIe 4.0 x4/x2 SSD support) (M2P_SB) 4 x SATA 6Gb/s connectors
RAID	RAID 0, RAID 1, RAID 5, and RAID 10 support for SATA storage devices
Audio	1 x front panel audio header 2 x audio jacks

Basic Information

Internal I/O Ports	1 x 24-pin ATX main power connector 1 x 8-pin ATX 12V power connector 1 x 4-pin ATX 12V power connector 1 x CPU fan header 3 x system fan headers 2 x addressable LED strip headers 2 x RGB LED strip headers 2 x M.2 Socket 3 connectors 4 x SATA 6Gb/s connectors 1 x front panel header 1 x front panel audio header 1 x USB Type-C header, with USB 3.2 Gen 2 support 1 x USB 3.2 Gen 1 header 2 x USB 2.0/1.1 headers 2 x Thunderbolt add-in card connectors 1 x Q-Flash Plus button 1 x reset button 1 x reset jumper 1 x Clear CMOS jumper
TPM (Trusted Platform Module)	1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module only)

Others

Special Features	Support for GIGABYTE Control Center (GCC) Support for Q-Flash Support for Q-Flash Plus
Bundled Software	Norton Internet Security (OEM version) LAN bandwidth management software

Warranty Information

Manufacturing Warranty	3 years
------------------------	---------