

## Dahua XVR1A08 8 Channel Penta-brid XVR

Sale Price: 5200.0



PRODUCT ID: 01951

### System

Main Processor	Embedded Processor
Operating System	Embedded LINUX

### Audio and Video

IP Camera Input	8CH: 8+2, each channel up to 5MP HDCVI Camera: 1080P@25/30fps, 720P@25/30fps AHD Camera: 1080P@25/30, 720P@25/30fps TVI Camera: 1080P@25/30, 720P@25/30fps CVBS Camera: PAL/NTSC
Two-Way Talk	Reuse audio in/out, RCA

### Display

Interface	1 HDMI ,1 VGA
Resolution	1920×1080, 1280×1024, 1280×720, 1024×768
Multi-Screen Display	When IP extension mode not enabled: 8CH: 1/4/8/9 When IP extension mode enabled: 8CH: 1/4/8/9/16
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording

### Recording

Compression	H.264
Resolution	1080N, 720P, 960H, D1, HD1, BCIF, CIF, QCIF
Record Rate	Main Stream- 8CH: the 1st channel 1080N/ 720P (1~25/30fps), others 1080N (1~12fps)/ 720P(1~15fps); 960H/ D1/ HD1/ BCIF/ CIF/ QCIF (1~25/30fps) Sub steram- CIF/QCIF (1~7fps)
Bit Rate	32Kbps ~ 4096Kbps Per Channel

## System

Record Mode	Manual, Schedule (General, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop
Record Interval	1 ~ 60 min (default: 60 min), Pre-record: 1 ~ 30 sec, Post-record: 10 ~ 300 sec

## Video Detection And Alarm

Trigger Event	Recording, PTZ, Tour, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips
Video Detection	Motion Detection, MD Zones: 396 (22 × 18), Video Loss, Tampering and Diagnosis

## Playback And Backup

Sync Playback	8CH: 1/4/9
Search Mode	Time /Date, Alarm, MD and Exact Search (accurate to second)
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Repeat, Shuffle, Backup Selection, Digital Zoom
Backup Mode	USB Device/Network

## Third Party Support

Third Party Support	Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek, and more
---------------------	--

## Network

Interface	1 RJ-45 Port (100M)
Network Function	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter ,DDNS, FTP, Alarm Server, P2P,IP Search (Supports IP camera, DVR, NVS, etc.)
Maximum User Access	128 users
Smart Phone	iPhone, iPad, Android
Interoperability	ONVIF 16.12, CGI Conformant

## Storage

Internal HDD	1 SATA Port, up to 6TB capacity
--------------	---------------------------------

## Auxiliary Interface

## System

USB	2 USB 2.0
-----	-----------

## Power

Power Supply	DC12V/1.5A
Power Consumption	<10W

## Component

### Environment

Operational Conditions	-10°C ~ +45°C (+14°F ~ +113°F), 10~ 90% RH
Storage Conditions	-20°C ~ +70°C (-4°F ~ +158°F), 0~ 90% RH

## Construction

Dimensions	Cooper 1U, 197mm×192mm×41mm (7.8"×7.6"×1.6")
Net Weight	0.55kg (1.2lb)
Gross Weight	1kg (2.2lb)