

Hikvision DS-7104HGHI-M1 4 Channel Turbo HD 1080P DVR

Sale Price: 3100.0



PRODUCT ID: 03559

Audio and Video	
IP Camera Input	Up to 5-ch IP camera inputs 1-ch (up to 5-ch) Up to 2MP resolution Support H.265+/H.265/H.264+/H.264 IP cameras
Two-Way Talk	Support all channels HDTV I two-way audio technology
Display	
Resolution	Analog Video Input-4-ch BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection HDTV I Input-1080p25, 1080p30, 720p25, 720p30 AHD Input-1080p25, 1080p30, 720p25, 720p30 HDCVI Input-1080p25, 1080p30, 720p25, 720p30 CVBS Input-Support HDMI Output-1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz VGA Output-1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz Video Output Mode-HDMI/VGA simultaneous output Audio Input-1-ch RCA (2.0 Vp-p, 1 KΩ) 4-ch via coaxial cable Audio Output-1-ch, RCA (Linear, 1 KΩ)
Recording	
Compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
Resolution	For 1080p stream access: 1080p Lite/720p Lite/WD1/4CIF/VGA/CIF For 720p stream access: 720p/WD1/4CIF/VGA/CIF For SD stream access: WD1/4CIF/VGA/CIF
Record Rate	Main stream: For 1080p stream access: 1080p Lite/720p Lite/WD1/4CIF/VGA/CIF@25 fps(P)/30 fps (N) For 720p stream access: 720p/WD1/4CIF/VGA/CIF@ 25fps (P)/30 fps (N) For SD stream access: WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) Sub-stream: 4CIF@15fps; CIF/QVGA@25 fps (P)/30 fps (N)
Bit Rate	32 Kbps to 4 Mbps
Others	Stream Type-Video, Video & Audio Audio Compression-G.711u Audio Bitrate-64 Kbps Audio over coaxial cable, motion detection

Playback And Backup	
Sync Playback	4-ch
Network	
Interface	SATA-1 SATA interface Capacity-Up to 4 TB capacity for each disk USB Interface-Rear panel: 2 × USB 2.0 64 Mbps
Ethernet Port	1, RJ45 10/100 Mbps self-adaptive Ethernet interface
Network Function	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, UPnP™, HTTPS
Power	
Power Supply	12 VDC, 1.5 A
Power Consumption	≤ 10 W (without HDD)
Component Environment	
Operational Conditions	Working Temperature -10 °C to 55 °C (14 °F to +131 °F)
Storage Conditions	Working Humidity 10% to 90%
Construction	
Dimensions	200 × 200 × 48 mm (7.9 × 7.9 × 1.9 inch) ≤ 0.8 kg (without HDD, 1.8 lb.)