

PROLiNK CAT6 NETWORKING CABLE (GRAY)



Regular Price: 5100.0

Sale Price: 4800.0

PRODUCT ID: 04976

— Connection Class

Standard	TIA/EIA-568A/568B & ISO 11801
Shielding Connector	UTP
Connector Type	23 AWG (4 pairs)
Category Connector	Cat6

Physical Specs

Dimensions	390 x 390 x 235mm (L x W x H) Easy-pull boxes/Cable length of 305M
Color	A White-Blue Stripe and a Blue B White-Orange Stripe and Orange C White-Green Stripe and Green D White-Brown Stripe and Brown

Cable Details

Conductor	Material: CCA (Copper content: 35%) Conductor Diameter: 0.56±0.02mm Conductor Resistance MAX 18Ω/100m at 20°C Mutual Capacitance: MAX 5600pf/100M Resistance Unbalance: MAX 5% Resistance Unbalance: MAX 300pf/100M
Insulation	Insulation: High-Density Polyethylene Insulation Diameter: 0.93±0.02mm Insulation Nominal Wall Thickness: 0.2mm Insulation Resistance: MIN 150MΩ/KM
Twisting	2 Insulated conductors twisted together

Technical Detail

Connection Class

Cable Designation	Cable Diameter: 5.6±0.15mm Printing: Each meter printed with a sequential length counter Jacket Nominal Wall Thickness: 0.7±0.01mm
Outer Diameter	Cable Diameter: 5.6±0.15mm
Weight	9.67kg/roll (Cable Only) 10.53kg (With Box)
Temperature ange	75°C