

DIGITAL X MP930S 3KVA Standard Backup Online UPS

Sale Price: 33000.0



PRODUCT ID: 01607

— Main Feature

Capacity	3000VA
Display Type	LCD
Load Capacity	2700W
Input Voltage	110±300Vac (176±264Vac @ 100% load)
Output Voltage	208/220/230/240Vac
Frequency (Battery Mode)	(50/60±0.1%)Hz
Battery	8 Battery with 12V / 8.2Ah
Others	LCD Display: Input voltage, Input frequency, Output voltage, Output frequency, Load percentage, Battery voltage, Inner temperature& Remaining battery backup time Frequency Range: 40±70Hz (50/60Hz Auto-Sensing) Backup Time (50% Load): 16Min, (Full Load): 5Min Charge time: 4 hours (To 90% of full capacity) Efficiency (Approx.): AC Mode / Line Mode: 91% Battery Mode: 88% Crest factor: 3:01 Output Waveform: Pure Sinewave Altitude: <1500m, derating required when±1500m Humidity: 20~95%RH @ 0~40°C (Non condensing) Operating Temperature: 0°C~40°C

Input Features

Power Factor	≥0.99
Voltage Range	110±300Vac (176±264Vac @ 100% load)

Output Features

Voltage Range	208/220/230/240Vac
Power Factor	0.9

Main Feature

Type of Wave

Pure Sinewave

Physical Specification

Dimension

191×460×337mm

Weight

Net: 26.01kg

Gross: 27.09Kg

Manufacture Warranty

Warranty

01-Year