

## KSTAR 650VA Offline UPS

Sale Price: 3650.0



PRODUCT ID: 03752

### — Main Feature

|                          |                                                                                                             |
|--------------------------|-------------------------------------------------------------------------------------------------------------|
| Capacity                 | 650VA                                                                                                       |
| Input Voltage            | 230Vac                                                                                                      |
| Output Voltage           | 230 (+/-10%)                                                                                                |
| Frequency (Battery Mode) | 50 Hz ±1 Hz                                                                                                 |
| Battery                  | 12V Battery<br>AC Voltage Regulation: 230+/-10%(Battery mode)<br>Frequency Range: 50 Hz ±1 Hz(Battery mode) |

### Input Features

|               |                                                  |
|---------------|--------------------------------------------------|
| Frequency     | 40 Hz (auto sensing) } } >> 40 Hz (auto sensing) |
| Voltage Range | 140 – 300 Vac                                    |

### Output Features

|               |                         |
|---------------|-------------------------|
| Backup Time   | Max. 12 Min(Standard)   |
| Voltage Range | 230 (+/-10%)            |
| Type of Wave  | Simulated Sine Wave     |
| Transfer Time | Typical 4-8ms, 13ms max |

### Physical Specification

|           |                  |
|-----------|------------------|
| Dimension | 301 x 101 x142.5 |
| Weight    | Approx. 4.3      |

### Manufacture Warranty

## Main Feature

### Warranty

### 1 Year Warranty

Under the following conditions, the warranty would not be provided:

- UPS burning due to thunder, abnormal overload, insect entrance and others.
- If ambient temperature should not be maintained at 20 to 26 degrees Celsius with proper dehumidification. (24/7)
- If the product is placed in a dusty and damp place.
- In the absence of Generator connectivity Without proper battery charge, the warranty will be void.
- Battery swelling and overcharging due to the wrong system voltage setting of the UPS.