

SANTAK Robust R650 650VA Offline UPS

Sale Price: 4000.0



PRODUCT ID: 05479

Main Feature

Capacity	650VA/360W
Frequency (Battery Mode)	50 Hz +/-1 Hz
Noise Level	Less than 40dB
Battery	2V/7Ah*1 VRLA Recharge time: 2-4hours to 90% capacity

Input Features

Frequency	>40Hz (comply with generator)
Power Factor	230 VAC
Voltage Range	140-300 VAC

Output Features

Backup Time	15 minutes
Voltage Range	+/-10%
Power Factor	230 VAC
Type of Wave	AC mode: pure sine wave; battery mode: simulated sine wave
Transfer Time	Typical 4-8ms

Physical

Specification

Dimension	100 x 278 x 143 mm
Weight	4,4 kg

Manufacture

Warranty

Main Feature

Warranty

2 years

Under the following conditions, the warranty would not be provided:

- UPS burning due to thunder, abnormal overload, insect entrance and others.
- If ambient temperature should not be maintained at 20 to 26 degrees Celsius with proper dehumidification. (24/7)
- If the product is placed in a dusty and damp place.
- In the absence of Generator connectivity Without proper battery charge, the warranty will be void.
- Battery swelling and overcharging due to the wrong system voltage setting of the UPS.